

GALVANIZED STEEL SUNLIT ROOF HATCH

CATEGORY: SHOP BY SIZE

SKU: BRHLB









TOLL FREE PHONE: 1-800-431-8651




info@bestroofhatches.com




FAX: 1-888-828-6021

www.BestRoofHatches.com

36.90" A 42.90"





SPECIFICATION

- (1) COVER: 11 GA ALUM COVER STIFFENED TO WITHSTAND A LIVE
 A LOAD OF 40PSF WITH A MAX DEFLECTION OF 1/150 OF THE SPAN
 - 2 LINER: 18 GA ALUM
 - (3) CURB AND COUNTERFLASH W/ EZ TAB:
 - 14GA GALV STEEL
 - 4 FINISH: RED OXIDE POWDER COAT
 - (5) SPRING/HINGE ASSEMBLY: ZINC PLATED STEEL TAMPER-PROOF HINGE CONTAINED WITHIN SPRING/HINGE ASSEMBLY. TELESCOPIC TUBES CONTAIN COIL STEEL COMPRESSION SPRINGS FOR LIFT ASSISTANCE

 - (7) LATCH: SINGLE POINT LATCH SLAM LATCH HOLDS COVER CLOSED AGAINST 20 PSF WIND UPLIFT. EXTERNAL PALM RELEASE INTERNAL RELEASE HANDLE WITH PADLOCK HASPS

 $\langle 8 \rangle$ insulation:

1" POLYSTYRENE (R4) IN COVER, AND 1" POLYISO (R7.2) IN CURB

GASKET: ADHESIVE BACKED EPDM RUBBER EXTRUSION

10 SIZING: WIDTH X LENGTH DIMENSIONS ARE MEASURED INSIDE CURB YOUR TO INSIDE CURB WHERE THE WIDTH IS HINGE TO LATCH AND LENGTH IS HINGED SIDE WITH SPRINGS

 ROOF HATCH SIZE
 36
 "(WIDTH) x
 30
 "(LENGTH)

 CLEAR OPENING
 25.94
 "(WIDTH) x
 29.50
 "(LENGTH)

 ROUGH OPENING
 36
 "(WIDTH) x
 30
 "(LENGTH)

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.

STAINLESS STEEL HARDWARE?

NO

PROJECT:

ARCHITECT:

CONTRACTOR:

QTY:

PART#:

BRHLB36X30S1P

TITLE:

Roof Hatch, SunLit Series,
Sngl Dr, Zinc Hidw,
Galvanized Steel Curb, Red Oxide Pwd and

NAME DATE SIZE DWG. NO.

ELW 10/15/12

DRAWN

RELEASED

Α

WEIGHT: VARIES

Aluminum Cover, Mill Finish, Sngl Wall Curb,

SHEET 1 OF 2

2