

GALVANIZED STEEL DOUBLE DOOR SAFEMAX™ SMOKE VENT, ROOFTOP CLOSE

CATEGORY: SMOKE VENTS
SKU: BSVSW-DNR









TOLL FREE PHONE: 1-800-431-8651




info@bestroofhatches.com



1-888-828-6021

www.BestRoofHatches.com



SECTION A-A

SPECIFICATIONS:

- (1) COVER: 14 GAUGE GALVANNEAL COVER STIFFENED TO WITHSTAND A LIVE LOAD OF 40 PSF WITH A MAX DEFLECTION OF 1/150 OF THE SPAN
- $\overline{2}$ **LINER**: 22 GAUGE GALVANNEALL
- (3) CURB AND COUNTERFLASH W/ EZ TAB: 14 GAUGE GALVANNEAL
- 4 FINISH: COVER- PWD COAT PAINT, HIGH REFLECTANCE WHITE CURB- PWD COAT PAINT, HIGH REFLECTANCE WHITE
- (5) GAS SPRING WITH DAMPER: DESIGNED TO OPEN AGAINST A 10PSF SNOW LOAD IN NOT LESS THAN 2 SECONDS
- (6) HOLD OPEN ARM: LOCK COVER IN FULLY OPEN POSITION 7INC PLATED STEEL
- (7) LATCH: ZINC PLATED ROTARY LATCH ASSEMBLY DESIGNED TO HOLD COVERS CLOSED AGAINST 90 PSF WIND UPLIFT ZINC PLATED STEEL LATCH STRIKERS ON COVERS

- (8) HINGES: ZINC PLATED STEEL WITH STAINLESS STEEL HINGE PINS
- (9) INSULATION: 1" POLYISOCYANURATE IN COVER AND AROUND CURB PERIMETER, R-VALUE 6
- (10) GASKET: ADHESIVE BACKED EPDM RUBBER EXTRUSION
- (11) THERMAL RELEASE MECHANISM: VENT COVERS OPEN
 THERMALLY BY HEAT AT FUSIBLE LINK TEMPERATURE 165 °F
- (2) MANUAL OPENING: VENT COVERS OPEN WITH INTERNAL AND EXTERNAL MANUAL PULL HANDLE, 1/16" DIA SST CABLE

SMOKE VENT SIZE 48 (WIDTH) x 96 (LENGTH)

CUL US

	PROJECT.										
	A	RCHITE	RCHITECT:								
CONTRACTOR: QTY:											
	PART#:				BSVSW	48	Χ	96	D1N	165	R
		TITLE: Smoke Vent, SafeMAX Series Galvanneal, Dbl Dr, Single Wall Curb Non-Electrical									
		NAME	DATE	SIZE	DWG. N						REV
	DRAWN	-	05/04/11	Α	BSVSW_X_D1N _R						-
	RELEASED	DS	05/04/11	WE	IGHT: VAF	RIES				SHEET 1 OF 2	

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.

2

1

PRO IECT