

GALVANIZED STEEL SINGLE DOOR SAFEMAX™ SMOKE VENT, ROOFTOP CLOSE

CATEGORY: SMOKE VENTS
SKU: BSVSW-SNR









TOLL FREE PHONE: 1-800-431-8651





info@bestroofhatches.com



FAX: 1-888-828-6021

www.BestRoofHatches.com








SPECIFICATIONS:


- (T) COVER: 14 GAUGE GALVANIZED STEEL COVER STIFFENED TO WITHSTAND A LIVE LOAD OF 40 PSF WITH A MAX DEFLECTION OF 1/150 OF THE SPAN
- (2) LINER: 22 GAUGE GALVANIZED STEEL
- (3) CURB AND COUNTERFLASH W/ EZ TAB: 14 GAUGE
- 4 FINISH: POWDER COAT PAINT, HIGH REFLECTANCE WHITE
- (5) GAS SPRING WITH DAMPER: DESIGNED TO OPEN AGAINST A 10PSF SNOW LOAD IN NOT LESS THAN 2 SECONDS
- (6) HOLD OPEN ARM: LOCK COVER IN FULLY OPEN POSITION ZINC PLATED STEEL
- (7) LATCH: ZINC PLATED ROTARY LATCH ASSEMBLY DESIGNED TO HOLD COVERS CLOSED AGAINST 90 PSF WIND UPLIFT ZINC PLATED STEEL LATCH STRIKERS ON COVERS


- (8) THERMAL RELEASE MECHANISM: VENT COVERS OPEN THERMALLY BY HEAT AT FUSIBLE LINK TEMPERATURE 165 °F
- (9) MANUAL OPENING: VENT COVERS OPEN WITH INTERNAL AND EXTERNAL MANUAL PULL HANDLE, 1/16" DIA SST CABLE
- HINGES: ZINC PLATED STEEL WITH STAINLESS STEEL HINGE PINS
- (1) INSULATION: 1" POLYISOCYANURATE IN COVER AND AROUND CURB PERIMETER, R-VALUE 6
- $\begin{tabular}{ll} \hline \end{tabular}$ Gasket: Adhesive backed epdm rubber extrusion on cover

SMOKE VENT SIZE 36 (WIDTH) x 30 (LENGTH)

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHBITED.







2