

GALVANIZED STEEL QUAD DOOR ACOUSTICMAX™ 48 SMOKE VENT, LINEAR ACUATOR WITH ELECTRICAL OPENING MECHANISM

CATEGORY: SMOKE VENTS
SKU: BSVX-Q2A









TOLL FREE PHONE: 1-800-431-8651



EMAIL: info@bestroofhatches.com



1-888-828-6021

www.BestRoofHatches.com

DETAILS

SOUND RATING(S) Independent third party tested to ASTM E90 and ASTM E1332 STC 48 - OITC 36

MATERIAL 14 gauge galvanneal steel; powder coat

FINISH High Reflectance White exterior cover with black interior liner and black curb

COVER Metal with liner, withstands a live load of 40psf with a max deflection of 1/150 the span

CURB Double wall curb with EZ tab counterflash and mounting flange

 ${\bf INSULATION}$ Mineral wool and sound mat in cover and curb, total R-10

GASKET Extruded EPDM adhesive backed gasket seals

HINGE Stainless steel heavy duty pintle hinge


SPRING Gas spring with damper opens cover against 10psf snow load

HOLD OPEN ARM Zinc plated steel automatic hold open arm locks cover in open position

LATCH Zinc plated steel rotary latch designed to hold covers closed against 90psf wind uplift

OPERATION Opens automatically with a fusible link and manual pull handles

CERTIFICATIONS UL 793 Listed



ORDER GUIDE

BASE	WIDTH	Χ	LENGTH	DOOR	CURB	ELECTRIC	LINK	TEMP (°F)	CLOSING	-	OPTIONS
BSVXG		Х								_	
	Standard Sizes (W x L)			D Double Door	2 Double Wall	N No Electrical	165	350	R Rooftop Close		OP1 Door Position Sensor
	30" x 30" 36" x 30" 36" x 36" 48" x 48" 48" x 72" 48" x 96" Additional size options			Q Quad Door	3 Curb Mount	L 24VDC/24VAC	212		W Manual Winch		B1A Burglar Bars
						H 110VAC / 240VAC 280 450		450	A Linear Actuator*		
	also avail	able	2.						*Voids UL		