

ALUMINUM ROOF HATCH - MIFAB

CATEGORY: ALUMINUM

SKU: RHA



TOLL FREE PHONE:
1-800-431-8651



EMAIL:
info@bestroofhatches.com



FAX:
1-888-828-6021

www.BestRoofHatches.com

Location: _____



RHA, RHG

ROOF HATCH

Specification: MIFAB® Series RHA and RHG roof hatches are designed to provide convenient, economical access to the roofs of buildings. They are available in either white prime coated galvanized steel (RHG) or aluminum (RHA). All hatches are designed with weather resistant gasketing to ensure long life, low maintenance and ease of operation. Roof hatches install easily over the roof opening and are secured from the base flange to the roof deck.

Material: RHG cover is 14 gage galvanized steel and 20 gauge steel liner. RHA cover is .090" aluminum with a .050 aluminum liner. The inside of the cover is gasketed with a neoprene weather seal to provide a flush, tight, fit. Covers are insulated with 1" (25) of fibreboard and are designed to support a snow load of 40 lbs. per square foot. The frame for the RHG Series is 14 gage galvanized steel and the frame for the RHA Series is .090" aluminum.

Curb: Curbs are 12" (305) high with 4" (102) wide rounded corner flashing flange complete with 1" (25) fibreboard insulation.

Hinge: Formed steel hinges with stainless steel pins.

Finish: RHG Series is a primed white finish. RHA Series is an aluminum mill finish.

Opening: Hydraulic column operators allow cover to open and close easily.

Device: Cover is equipped with an automatic hold open arm with a red vinyl grip release that keeps the cover in an open position when needed, and allows for easy control when lowering the latch cover.

Handle: Self latching outside cadmium plated steel turn handle with inside lever handle allows cover to always latch securely.

Latch: Locking hasps are located both inside and outside of the cover. All hardware is cadmium plated steel.

